

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY)

2. REPORT TYPE
Technical Papers

3. DATES COVERED (From - To)

4. TITLE AND SUBTITLE

5a. CONTRACT NUMBER

NIA

5b. GRANT NUMBER

5c. PROGRAM ELEMENT NUMBER

000000

6. AUTHOR(S)

5d. PROJECT NUMBER

CIAO

5e. TASK NUMBER

001X

5f. WORK UNIT NUMBER

549816

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048

8. PERFORMING ORGANIZATION
REPORT

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048

10. SPONSOR/MONITOR'S
ACRONYM(S)

11. SPONSOR/MONITOR'S

NUMBER(S) AFRL-PR-

ED-TP-2001-004

12. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES

14. ABSTRACT

20030310 024

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:

a. REPORT

Unclassified

b. ABSTRACT

Unclassified

c. THIS PAGE

Unclassified

17. LIMITATION
OF ABSTRACT

A

18. NUMBER
OF PAGES

19a. NAME OF RESPONSIBLE
PERSON

Leilani Richardson

19b. TELEPHONE NUMBER

(include area code)

(661) 275-5015

DTSV

1184741511

MEMORANDUM FOR PRS (In-House Publication)

~~CIA0001X~~

CIA0001X

3003

11

FROM: PROI (STINFO)

All of Merrell's JONs

03 Jan 2001

JOC 3, but

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-TP-2001-004
Merrell, Joe, "AFRL Propulsion Directorate Test Facilities"

assigned an
acc.# for a TR


Presentation for Visitors/Prospective Customers to AFRL/Edwards


(Statement A)

Air Force Research Laboratory Location


DISTRIBUTION STATEMENT A
Approved for Public Release
Distribution Unlimited

NOTE:
CHANGES FROM PREV.
REVIEWS ARE HI-LITED
IN YELLOW.





DRAFT 24-Nov-80 Air Force Research Laboratory Propulsion Directorate Facilities




DRAFT 24-Nov-00



Propulsion Directorate

Satellite Propulsion



- To 5,000lb Thrust
- Horizontal Single Axis
- LOX/GOX/Hydrazine/NTO

• HEDM

Experimental Systems



• ATLAS
• SATURN V

Small Solid Components




- To 36,000lb Thrust
- Horizontal Single Axis (Spin Capable)
- Temp Conditioned 30° to 120°F

- MM I / MM III
- MX
- SICBM
- KKV

TO 10,000,000 LB THRUST FIXED OR SPIN HORIZONTAL OR VERTICAL ORIENTATION ENVIRONMENTAL CONDITIONING HIGH HAZARD

- To 1,500,000lb Thrust
- Horizontal or Vertical Single Axis
- Dual Position (Expandable to Quad and 6,000,000lb Thrust)

Large Systems Complex



- SATURN V
- TITAN IVD
- TITAN 34D

- To 8,000,000lb Thrust
- Vertical Multi Axis
- Temp Conditioned 25° to 100°F
- Humidity Conditioned at 40%


High Thrust (Solid and Liquid)



- TITAN IVD
- SUPER HIPPO
- R.R. TANK CAR

- To 10,000,000lb Thrust
- Horizontal or Vertical Multi Axis
- LOX/Hydrogen/Hydrazine/NTO


High Hazard (Solid)



- 2.75 RAP
- MINI RPV
- MX
- F-16 HYDRAZINE TANK
- SHUTTLE STORAGE VESSELS

- To 4,000,000lb Thrust
- Horizontal Single Axis
- Temp Conditioned 30° to 120°F


Large Liquid Components



- ABRES
- SICBM
- PEACKEEPER
- STAR TECH

- To 300,000lb Thrust
- Horizontal and Vertical Single Axis
- Temp Conditioned 30° to 120°F
- LOX/GOX/Hydrogen/Hydrazine/NTO

Large Solid Components



- SERGEANT
- STARBIRD
- VIPER
- F-16 LIVE FIRE
- MX
- BULL PUP


- To 300,000lb Thrust
- Horizontal and Vertical Multi Axis
- Temp Conditioned 30° to 120°F
- Spin Capable

DRAFT 24-Nov-00

Propulsion Directorate




Satellite Propulsion



- MILSTAR

- 6 Hours at 125,000 Feet
- Horizontal Single Axis to 1,000lb Thrust
- LOX/GOX/Hydrogen/Hydrazine/NTO

Space Experiments (SPEF)




- CENTAUR
- STM/TTM
- MSTI
- GOSSAMER TORUS

- Continuous at 650,000 Feet (Sim)
- Temp Conditioned -300 to +400
- IR/UV Solar Simulation

TO 650,000 FEET SIMULATION
TO 60,000 LB THRUST (FIXED OR SPIN)
HORIZONTAL OR VERTICAL

ORIENTAL
ENVIRONMENTAL CONDITIONING


Space Propulsion (Liquid)



- AGENA
- JPL STORABLE PROPULSION
- STAR TECH
- XLR-132
- SKYBELT

- 20 Minutes at 110,000 Feet (Sim)
- Vertical Single Axis to 50,000lb Thrust
- LOX/Hydrazine/NTO


Space Propulsion (Solid)



- TRIDENT C4
- SICBM
- HAST
- PEACEKEEPER
- AIR AVG
- DELTA V

- 20 Min at 110,000 Feet (Sim)
- Horizontal Multi Axis to 60,000lb Thrust
- Fixed or Spin Capable

Electric Propulsion



- ESEX
- ELITE

- Continuous at 650,000 Feet (Sim)
- Temp Conditioned -300 to +400
- IR/UV Solar Simulation

Space Propulsion (Solid)



- KHIT
- AIS
- VIPER
- ASAS


- To 110,000 Feet (Sim)
- Horizontal Multi Axis to 50,000lb Thrust
- Contained Exhaust

DRAFT 24-Nov-00

Propulsion Directorate



Flow Laboratory



- To 3,500 PSI and 16" Pipe
- 3 Isolated Water Systems
- To 32 GPM
- Flow and Mass Mixture Ratio
- Particle Sizing

Plume Studies




- SIDEWINDER
- SICBM
- SERGEANT
- VIPER

- Near IR/Visible/UV
- Horizontal or Vertical Orientation
- Temperature Mapping
- Particle Collection


VEHICLE FLIGHT/HOVER TESTING REDUCED SMOKE PROPULSION STUDIES SOLAR THRUSTER EXPERIMENTS SATELLITE g LOAD STUDIES TETHERED LAUNCH CAPABILITY

Solar Laboratory



- To 5,000 F
- 24 X 32 Autotrack HelioStat
- 10,000 to 1 Concentrator
- Continuous at 0.1 PSIA


• SOLAR THRUSTER



- KHIT
- KKV
- LEAP
- ASAT
- SCIT

- Enclosed Flight Bay (70 X 40 X 30)
- Temp Conditioned -20 to +130 F
- Static Test Stand (Pre-Flight)
- Cleanroom Integration Capability
- Optical Target 800 Meter From Bay


Centrifuge



- 2.75
RAP

- To 48 g at 21 Feet
- To 82 RPM
- To 30,000lb Test Article
- Temp Conditioned -300 to 500 F
- Humidity Conditioned to 95%

Silo



- MM

- Dual Silos
- 26 Feet Dia X 86 Feet Deep



DRAFT 24-Nov-00

Satellite Engine Complex

Area 1-14



GENERAL AREA CAPABILITIES:

- Propane-fired steam/vacuum system, up to 6 hours run time, 120 Kft simulated altitude
- Mechanical pump/diffusion system can be connected to C, D, E Chambers and Pump up to 700 Kft Simulated Altitude
- Four Data Acquisition Systems:
- 6000 psi GN2, Ample Water, LN2, LOX, GH2, Propane Tankage


CELL CAPABILITIES: (current config)

- Each Chamber / Stand Rated to 425 lb of 1.1 TNT Equivalent Liquid Propellant
- 4 Vacuum Chambers for Engine/Component Testing

- A Cell - 1000 Lbf Thrust, 125 Kft Alt.
- C Cell - 100 Lbf Thrust, 700 Kft Alt.
- D Cell - No Thrust Stand, 260 Kft Alt.
- E Cell - 300 Lbf Thrust, 260 Kft Alt.

• 3 Ambient Thrust Stands

- A Cell - 15K Lbf Horizontal
- B Cell - 15K Lbf Horizontal
- D Cell - 5 Lbf HEDM Vertical



Testing History:

- Milstar Thruster
- Microcosm Low-Cost Engine
- Stoichiometric Gas Generator
- AeroAstro Low Cost Engine 1998
- X-34 Fastrack Injector 1997
- SSME Pre-Burner Injector 1997
- High Energy Density Materials Microthruster (HEDM)
- 5lb Thruster Certification
- 300lb Thruster Certification
- Atlas Vernier
- NASP 1990-91
- 100lb Thrusters Shuttle
- Nose Thruster
- Small Cryogenic Engine

DRAFT 24-Nov-00

Satellite Engine Complex Area 1-14




GENERAL AREA CAPABILITIES:

- Propane-fired steam/vacuum system, up to 6 hours run time, 120 Kft simulated altitude
- Mechanical pump/diffusion system can be connected to C, D, E Chambers and Pump up to 260 Kft Simulated Altitude
 - C chamber can achieve 700Kft
- Three Data Acquisition Systems
 - LABVIEW (2): 128 ch/100K Samples/Sec Throughput
 - NEFF 470: 32 Channels/10K Samples/Sec Throughput
- 6000 psi GN2, Ample Water, LN2, LOX, GH2, Propane Tankage
- Solar Laboratory
- 0 to 48 G Centrifuge
- Flow Laboratory
 - 2800 GPM @750 psi

CELL CAPABILITIES:


- Each Cell Rated to 425 lb of 1.1 TNT Equivalent Liquid Propellant
- Chamber A max thrust 5K lbf, horizontal
 - Current config - 1000 lbf thrust, 9' x 31' chamber, 120 Kft Altitude
- Chamber C max thrust 200 lbf, horizontal
 - current config - 100 lbf thrust, 7' x 12' chamber, 700 Kft Altitude
- Chamber D max thrust 5K lbf, horizontal
 - current config - No thrust stand in Chamber, 8' x 16' chamber, 260 Kft Altitude
- Chamber E maximum thrust 5K lbf, vertical
 - current config - 300 lbf thrust, 9' x 20' chamber, 260 Kft Altitude
- 3 Ambient Thrust Stands
 - A Cell - 15K lbf horizontal, thrust stand
 - B Cell - 15K lbf horizontal, thrust stand
 - D Cell - 5 lbf vertical, thrust stand

Area 1-14





Area 1-14



DRAFT 24-Nov-00


Satellite Engine Complex Test Cell A



ADDED SLIDE

CAPABILITIES:

- Ground level and altitude testing
 - Altitude simulation to 120,000 feet
 - Maximum run time; 6 hours
 - Chemical steam generator
- Maximum thrust
 - Altitude; 5,000 lbs, horizontal
 - Ground level; 15,000 lbs, horizontal
- Current thrust
 - Altitude; 1,000 lbs, horizontal
 - Ground level; 15,000 lbs, horizontal
- Cell 27 feet x 31 feet x 19 feet high
- Chamber 8.5 feet diameter x 31 feet long
- 1,000 lb overhead traveling crane
- Propellants
 - LO2; 500 gal @ 1,500 psi
 - GH2; 300 CuFt Water volume, maximum 3000 psi
- 425 lbs of TNT equivalent 1.1 class propellant



TESTING HISTORY:


- 100 lb Space Shuttle Nose Thruster 1970's
- NASP 1990 - 1991
- Stoichiometric Gas Generator 1998
- Throttling Altitude Engine 1962 - 1965
- Small Cryogenic Engine

DRAFT 24-Nov-00


Fuel Rich Gas Generator 1-14 A Cell



ADDGD SLIDE



DRAFT 24-Nov-00



Satellite Engine Complex Test Cell B




ADDED SLIDE

CAPABILITIES:

- Ground level testing
- Maximum thrust; 20,000 lbs, horizontal
 - Current configuration; 20,000 lbs, horizontal
- Cell 27 feet x 31 feet x 19 feet high
- Propellants
 - LO₂; 1,400 gal @ 1,100 psi
 - RP1; 1,400 gal @ 1,100 psi
- 425 lbs of TNT equivalent 1.1 class propellant

TESTING HISTORY:

- Atlas Vernier Engine 1994 - 1995
- Aero Astro Engine 1998
- Microcosm Low-Cost Engine
- High Energy Density Materials Microthruster (HEDM)



DRAFT 24-Nov-00

AeroAstro, 1 Mar 95

1-14 B Cell

ADD SP SLIDE



DRAFT 24-Nov-00


Satellite Engine Complex Test Cell C



CAPABILITIES:

- Altitude testing
 - Altitude simulation to 700,000 feet
 - Mechanical and diffusion pumps
- Maximum thrust; 200 lbs, horizontal
 - Current Configuration; 2 Each 10 lb thrust stands
- Cell 27 feet x 31 feet x 19 feet high
- Chamber 12 feet diameter x 7 feet long
- Propellants
 - N₂H₄; 6 tanks, 40 gal @ 1,350 psi
 - LN₂; 1 tank, 1000 gal @ 125 psi
 - 425 lbs of TNT equivalent 1.1 class propellant

ADDED SLIDE



TESTING HISTORY:


- MILSTAR 5 lb Thruster Certification, early 80's
- Teflon pulsed plasma thruster, 1970's

DRAFT 24-Nov-00

5 lb Thruster "Life Test"

1-14 C Cell

ADD SD SDC



DRAFT 24-Nov-00


Satellite Engine Complex Test Cell D



ADDED SLIDE


CAPABILITIES:

- Altitude Testing
 - Altitude simulation to 260,000 feet
 - Mechanical and diffusion Pumps
- Maximum thrust; 1,000 lbs, horizontal
 - Current configuration; no thrust
- Cell 27 feet x 31 feet x 19 feet high
- Chamber 8 feet diameter x 16 feet long
- Propellants
 - N_2O_4 ; 2 tanks, 75 gal @ 1,400 psi, 2,000 psi
 - N_2H_4 ; 2 tanks, 75 gal @ 1,500 psi
 - Glycol Conditioning -24F To +155F
 - LN_2 ; 2 tanks, 1,000 gal @ 125 psi
- 425 lbs of TNT equivalent 1.1 class propellant



TESTING HISTORY:


- 300 lb Hydrazine Thruster Certification
- High Energy Density Materials (HEDM) 1991 - 1992
- Milstar Pulsiong Bipropellant Engine, early 90's



High Energy Density Materials (HEDM) 1-14 D Cell



ADDED SLIDE



DRAFT 24-Nov-00


Satellite Engine Complex Test Cell E



CAPABILITIES:

- Altitude testing
 - Altitude simulation to 260,000 feet
 - Mechanical and diffusion pumps
- Maximum thrust; 5,000 lbs, vertical
 - Current configuration; 300 lbs, vertical
- Cell 27 feet x 31 feet x 19 feet high
- Chamber 9 feet diameter x 20 feet long
- Propellants; shared with D cell
 - N_2O_4 ; 2 tanks, 75 gal @ 1,400 psi, 2,000 psi
 - N_2H_4 ; 2 tanks, 75 gal @ 1,500 psi
 - Glycol Conditioning -24F To +155F
 - LN_2 ; 2 tanks, 1,000 gal @ 125 psi
- 425 lbs of TNT equivalent 1.1 class propellant

ADD SCITE




TESTING HISTORY:

- 300 lb Hydrazine Thruster Certification



DRAFT 24-Nov-2000 300 lb Thrust N_2H_4 Orbit Adjust Engine



ADDED
SIDE


DRAFT 24-Nov-00

Flow Laboratory Area 1-14



CAPABILITIES:

- Multi-element injector to 1100 psi and 2800 gpm
- Single element Injector to 2000 psi and 32 gpm
 - Modern optical design
 - Flow visualization
 - Flexible changeout
 - Mass patternization
 - Simulation for liquid
- Flow checkout facility
- Modern optical diagnostics
- Flow visualization
- Flexible change-out capability to accommodate different kinds of injectors
- Mass patternization via 27 element transversable linear array
- Simulation of liquid rocket engine manifold cross flow effects
- Flow checkout facility to verify injector design prior to hot firing




PAST TESTING:

- XLR-132 Injector
- Microcosm Injector

FUTURE TESTING:

- Integrated Powerhead Pre-Burner Injector
- Rocketdyne Hybrid Injector
- Pac-Astro Injector
- Arcjet Platelet Injector
- X-34 Fastrack Injector 1997
- SSME Pre-Burner Injector 1997



DRAFT 24-11-1990

Flow Laboratory, Area 1-14 High Pressure Injector Characterization Chamber Facility



GENERAL AREA CAPABILITIES:

- Unique facility provides full scale, single element windowed cold flow Injector test capability up to 2000 psi
- Injector change-out capability to test most injector geometries
- Simulate engine injector manifold cross flow effects
- Drop size and velocity measurement capability

LAB CAPABILITIES:


- 2000 psi, 10 ft³ chamber
- Liquid flow rates to 32 gpm
- Modern optical diagnostics
 - Malvern line-of-sight fraunhofer diffraction instrument
 - Aerometrics phase doppler particle analyzer
 - Coaxial beam particle analyzer
 - Greefield imaging particle analyzer
- Flow visualization
- Spray mass distribution measurements with 27 element traversable array

High Pressure Injector Characterization Chamber


Injector Design Methodology



LASER DROPLET DIAGNOSTICS




2000 psi PRESSURE VESSEL



GOALS

- Cost Effective Evaluation of Injector Designs
- Characterize the Effects of Injector Design Features on Performance and Stability



TYPICAL IMPINGING INJECTOR SPRAY

ACCOMPLISHMENTS

- In-House Testing 2000 PSI
- Atomization and Mixing Capabilities
- State of the Art Laser Measurements
- Manifold and Orifice Hydraulics


DRAFT 24-Nov-00



Solar Laboratory Area 1-14

CAPABILITIES:

- 10,000 : 1 Concentrator
- 32'x 2' sun tracking heliostat
- 25 kilowatt concentrator, up to 5800 degrees fahrenheit
- 2.5 gram/sec hydrogen or 5 gram/sec helium propellant flow rates
- 1lb thruster stand
- 30" x 30" chamber
- 750 Kft altitude
- 32 Channel, 10kHz, NEFF 470 data acquisition system
- 6000 psi GN2



TESTING HISTORY:

- Black Body Cavity Receivers with Secondary Concentrators Attached
- Porous Disk Test Bed
- Solar Bi-Modal Cavity Receiver
- Video Flux Mapper, Water Filled Calorimeter
- Rhenium Tube Cavity Thruster
- Reticulated Vitreous Carbon Calorimeter

DRAFT 24-Nov-00



Rigidized Concentrators



1.2 meter Rigidized


DRAFT 24-Nov-00



Centrifuge Facility Area 1-14


CENTRIFUGE CAPABILITIES:

- **Maximum G range**
 - 0 to 30 g at 13 foot radius
 - 0 to 48 g at 21 foot radius
- **0 to 82 RPM**
- **Acceleration to 30 g in 5 minutes**
- **60,000 lb total capability**
- **Environmental capability**
 - (-300 to +500 degree F)
 - 0 to 95 percent humidity



TESTING HISTORY:

- **Solar Parabolic Dish**
- **2.75 mm Rocket Assisted Projectile (RAP)**



DRAFT 24-Nov-00 Solid Propellant Preparation Cutting and Aging Facility, Area 1-21




GENERAL AREA CAPABILITIES:

- Originally designed to test liquid rocket engines for research aircraft (X-15, X-1, X-2)
- 6,000 psi GN2 cross country line
- 14 inch water main
- 440 VAC facility power
- Mechanical shop with 2 ton crane


CELL CAPABILITIES: (current config)

- Cell 1 - 425 lbs. of 1.1 solid propellant
 - Prepare tensile test specimens
- Cell 2 - 100 lbs. of 1.1 solid propellant
 - Rough cutting large pieces of propellant
- Cell 3 - 50 lbs. of 1.1 solid propellant
 - Explosion resistant window
- Cell 4 - Office / control room for Cells 1, 2, and 3
- Cell 5 - 75 lbs. of 1.1 solid propellant
 - Initial weighing, measuring, and trimming
 - Fragmentation testing
- Cell 6 - Control room for cells 5 and 7
- Cell 7 - 425 lbs. of 1.1 solid propellant
 - 4 environmental aging chambers
- Cell 8 - 20 lbs. of 1.1 solid propellant
- Cell 12 - 100 lbs. of 1.1 solid propellant
 - Environmental propellant storage



TESTING HISTORY

- Project Showboat
- Solid propellant Aging
- Ignition Delay
- Charged Nozzle



DRAFT 24-Nov-00 Solid Propellant Laboratory Complex Area 1-30




GENERAL AREA CAPABILITIES:

- Designed to formulate, mix, cast, cure and study, high energy propellants
- Environmental conditioning
- 6,000 psi GN2 cross country line
- 6 Inch water main
 - 50,000 gallon water storage
- 440 VAC and 28 VDC stand power
- Data acquisition and control system
- Over 30 mechanical shop buildings, preparation cells, and test stands


COMPLEX CAPABILITIES: (current configuration)

- Propellant storage bunkers, 10 each
 - Maximum 5,000 lb of 1.1 propellant
- Propellant aging cells, 12 each
 - Heat and humidity controlled
- Propellant processing cells, 11 each
 - Processing propellants, binders, and plasticizers
 - Maximum of 100 lb of 1.1 propellant per cell
- Propellant evaluation facility,
 - Tensile testing
 - Strand burning
- Propellant test stands and cells



TESTING HISTORY:

- Microwave Burner 1986 - 1987
- Combustion Stability 1983 - 1987
- Sidewinder Reduced Smoke
- Maverick Reduced Smoke
- Rotating Valve 1981
- 40mm RAP 1972
- 20mm RAP 1973
- 30mm RAP 1974
- Titan Failure Study 1986
- PeaceKeeper Stage I 1976
- PeaceKeeper Stage II 1976
- PeaceKeeper Stage II Failure Study 1982
- PeaceKeeper Stage III Failure Study 1985
- HMX Studies (Hardened structure Munitions) 1974



DRAFT 24-Nov-00 Solid Propellant Laboratory Complex Area 1-30



GENERAL AREA CAPABILITIES:

- Designed to formulate, mix, cast, cure and study, high energy propellants
- Environmental conditioning
- 6,000 psi GN2 cross country line
- 6 Inch water main
 - 50,000 gallon water storage
- 440 VAC and 28 VDC stand power
- Data acquisition and control system
- Over 30 mechanical shop buildings, preparation cells, and test stands

COMPLEX CAPABILITIES:

- Propellant storage bunkers, 10 each
 - Earth covered bunker
 - Above ground bunker
 - Maximum 5,000 lb of 1.1 propellant
- Propellant aging cells, 8 each
 - Heat and humidity controlled
 - From (-65 to +500) degrees F
- Propellant processing cells, 11 each
 - Processing propellants, binders, and plasticizers
 - Speed and temperature controlled mixers
 - Blast proof windows or remote television monitors
 - Maximum of 100 lb of 1.1 propellant per cell
 - Some limited to 25 lb

COMPLEX CAPABILITIES (continued):

- Propellant evaluation facility
 - Tensile, friction, and drop weight testing
 - Rheometrics mechanical and stress spectrometers
 - Strand burning
- Propellant test stands and cells
 - Test cell 25
 - Pulling and twisting tensile tester
 - Test cell 26
 - Combustion bomb window
 - Test cell 27
 - 60,000 volt electrostatic discharge testing
 - Test stand 34
 - Fluid energy mill
 - Test stand 44
 - Propellant burn sensitivity


TESTING HISTORY:


- 20, 30, 40mm RAP 1972-1974
- Maverick
- Rotating Valve 1981
- Combustion Laser
- HMX Studies (Hardened Structure Munitions) 1974
- Sidewinder
- Rotating Valve
- PeaceKeeper 1976-1985
- Titan



DRAFT 24-Nov-00


Solid Propellant Laboratory Complex Area 1-30






DRAFT 24-Nov-00

Solid Propellant Laboratory Complex Area 1-30






Propellant Aging Cells Area 1-30



CELL CAPABILITIES:

- Ground level environmental aging, 12 cells
 - Each cell is approximately 64 cubic feet
 - Temperature control From -65 to +500 degrees F.
 - Humidity control
- 2,400 lb of 1.1 TNT equivalent propellant total for 12 cells
- Remote environmental conditioning system
 - Data acquisition and health monitoring



TESTING HISTORY:

THIS
PAGE
IS
MISSING
IN
ORIGINAL
DOCUMENT

003.2

DRAFT 24-Nov-00

Motor Component Complex Area 1-32

GENERAL AREA CAPABILITIES:

- Plume diagnostics analysis system
- High hazard motor / propellant testing
- Hydrogen injector system
- Environmental conditioning
- 5,000 psi GN2 cross country line
- 6 inch water main
- 440 VAC and 28 VDC stand power
- Data acquisition and control system
- Mechanical shop with 2 ton crane
- Receiving and inspection station
 - 50 ton crane
 - Environmental conditioning

STAND CAPABILITIES: (current config)

- Pad 1 - 250,000 Lbf thrust, horizontal
- Pad 2 - 150,000 Lbf thrust, horizontal
- Pad 3 - 10,000 Lbf thrust, horizontal
- Pad 5A / 5B / 5C - 36,000 Lbf thrust, horizontal



TESTING HISTORY:

- Sidewinder
- Shuttle
- Small ICBM
- Hydrogen Augmented Solid Rockets
- Ammonium Perchlorate
- Minuteman
- PeaceKeeper
- Taurus
- Sparrow
- HIPPO
- Titan





Motor Component Complex Area 1-32



GENERAL AREA CAPABILITIES:

- 6,000 psi GN2 cross country line
- 6 inch water main
- 440 VAC and 28 VDC stand power
- Data acquisition systems
 - LabView; 64 channels, 100,000 samples/sec
- Control systems
 - Allen-Bradley; programmable logic controller
- Mechanical shop with 2 ton crane
- Receiving and inspection station
 - 50 ton crane
 - Environmental conditioning

TEST STAND CAPABILITIES:


- Ground level testing
 - Environmental conditioning
 - Horizontal or vertical orientation
- PAD 1 - maximum thrust 1M lbf.
- (Current configuration) 250,000 lbf. thrust
 - 10 ton overhead crane, 7,000 lb of 1.1 or 50K of 1.3 solid propellant
- PAD 2 - maximum thrust 1M lbf.
- (Current configuration) 150,000 lbf. thrust
 - 15 ton overhead crane, 7,000 lb of 1.1 or 50K of 1.3 solid propellant

TEST STAND CAPABILITIES:

- PAD 3 - maximum thrust 60,000 lbf.
- (Current configuration) no thrust, 1,000 lb of 1.1 or 5K of 1.3 solid propellant
 - High hazard motor / propellant / gun testing
- PAD 5A / 5B / 5C - maximum thrust 36,000 lbf.
- 70 lb of 1.1 or 180 lb of 1.3 solid propellant
 - Onboard automatic calibration system 99.9% accuracy
 - Pad 5A (Current configuration) 12,000 lb thrust,
 - Plume diagnostics analysis system
 - Pad 5B (current configuration), 10,000 lb thrust
 - Pad 5C 36,000 lbf. thrust, spin capability,
 - Hydrogen injection system

TESTING HISTORY:

- Sidewinder
- Sparrow
- Ammonium Perchlorate
- Small ICBM
- Minuteman
- Hydrogen Augmented Solid Rockets
- Minuteman
- PeaceKeeper
- Pegasus
- 30mm RAP
- Shuttle
- Taurus
- Durandahl
- HIPPO
- 20mm RAP



DRAFT 24-Nov-00


Large Motor Test Stand

Area 1-32 Test Stand 1



CAPABILITIES:

- Ground level testing
- Maximum thrust 1,000,000 lbf. horizontal or vertical
- Current thrust
 - 250,000 lbf. horizontal, six-component, automatic calibration
 - 25,000 lbf. side force
- 30' x 45' concrete pad
- 7,000 lb of 1.1 or 50,000 lb of 1.3 solid propellant
- Environmental enclosure (temperature / humidity)
- 10 ton traveling overhead crane




TESTING HISTORY:

- Minuteman
- Titan
- PeaceKeeper
- Viper
- SuperBATES
- Trident



DRAFT 24-Nov-00

Large Motor Test Stand Area 1-32 Test Stand 1




Thrust Vector Control (TVC) Test

DRAFT 24-Nov-00


Large Motor Test Stand

Area 1-32 Test Stand 1



Nozzleless Booster 1985

DRAFT 24-Nov-00




Large Motor Test Stand

Area 1-32 Test Stand 2




CAPABILITIES:

- Ground level testing
- Maximum thrust 1,000,000 lbf. horizontal or vertical
- Current thrust
 - 150,000 lbf. horizontal single axis, automatic calibration
 - 99.85 % thrust measurement accuracy
 - 1 to 4 segments, up to 34 inch diameter
- 30' x 45' concrete pad
- 7,000 lb of 1.1 or 50,000 lb of 1.3 solid propellant
- Environmental enclosure (temperature / humidity)
- 15 ton traveling overhead crane



TESTING HISTORY:

- High Internal Pressure Producing Orifice (HIPPO)
- Small ICBM (TVC Shoot Off)
- 84" Diameter, Materials Testing Motor (CHAR)
- SuperBates



DRAFT 24-Nov-00


High Hazards Test Stand

Area 1-32 Test Stands 3A, B, C, & D




CAPABILITIES:

- Maximum thrust 10,000 lbf, horizontal
- Current thrust
 - No thrust stand installed
- 1,000 lb of 1.1 or 5,000 lb of 1.3 solid propellant
- 2 ton traveling overhead crane
- Gun target



TESTING HISTORY:


- Sidewinder
- Sparrow
- 30mm RAP
- 20mm RAP
- Ammonium Perchlorate
- Hot Gas Valve• Durandahl
- F16 Emergency Hydrazine Generator
- Minuteman Critical Diameter Definition




DRAFT 24-Nov-0

High Hazards Test Stand


Area 1-32 Test Stand 3A




Integrated Stage Thrust Vectoring Test, 1982




High Hazards Test Stand 3A Test Area 1-32




Remotely Piloted Vehicle



DRAFT 24-Nov-04 High Hazards Test Stand 3A Test Area 1-32



30mm Rocket Assisted Projectile (RAP)




DRAFT 24-Nov-15 15 & 70 lb BATES Motor Pads - Area 1-32 Pads 5A, 5B, & 5C



CAPABILITIES:

- 70 lb of 1.1 or 180 lb of 1.3 solid propellant
- Onboard automatic calibrating system 99.9% accuracy
- One to four segments, up to 14 inch diameter
- Test stand 5A
 - Maximum thrust 12,000 lbs; current thrust 12,000 lbs
 - Plume diagnostics system
 - Mean particle sizing
 - Particle capture
 - Visible UV & IR
 - Thermal image recording
 - 3 Wideband IR radiometers
 - Near IR fourier transform spectrometer
- Test stand 5B
 - Maximum thrust 10,000 lbs; current thrust 10,000 lbs
- Test stand 5C
 - Maximum thrust 36,000 lbs; current thrust 36,000 lbs
 - Motor Spinning Capability
 - Hydrogen Injection System




TESTING HISTORY:

- Sidewinder
- Sparrow
- Shuttle
- Minuteman
- Durandahl
- Hydrogen Augmented Solid Rockets
- Titan
- PeaceKeeper
- Small ICBM
- 30mm RAP
- 20mm RAP
- Ammonium Perchlorate

מחזורי תכנון

מחזורי תפילה

**BATES Motor Pad
Area 1-32, Pad 5A**



15 lb Bates / Plume Test

DRAFT 24-Nov-00

Motor Behavior Complex Area 1-36



GENERAL AREA CAPABILITIES:


- 6,000 psi GN2 cross country line
- 16 in. water line to 100,000 gal source
- 440 VAC and 28 VDC stand power
 - Accessible for A and B pads, available for D pad
- Mechanical shop
 - With 2 ton traveling overhead crane

TEST STAND CAPABILITIES:

- Ground level testing
- Storable and solid propellant
- 1-36A Pad, maximum thrust, 4M lbf., horizontal
 - 1M Lbs TNT equivalent
- 1-36B Pad, inactive
- 1-36D Pad, explosive detonation studies
 - 1M Lbs TNT equivalent

TESTING HISTORY:

- PeaceKeeper Flight Termination Guidance
- Stage I / II / III 1980 -
- PeaceKeeper Advanced Development Program
- Titan III, 120 Inch Solid
- Ammonium Perchlorate
- Silo Fire Safety
- Solid Propellant Hazards Study (SOPHY)



DRAFT 24-Nov-00

Motor Behavior Complex Area 1-36, Horizontal Test Pad A




CAPABILITIES:

- Ground level testing
- Storable and solid propellant
- Horizontal bermed bare pad
- Maximum thrust, 4M lbf.
- 1M Lbs TNT equivalent

TESTING HISTORY:

- PeaceKeeper Flight Termination Ordinance Stage I / II 1980 -
- PeaceKeeper Ordnance Advanced Development Program
- Titan III, 120 Inch Diameter, Solid Strap On
- Minuteman Stage II
- Minuteman Stage III



DRAFT 24-Nov-00

Motor Behavior Complex Area 1-36, Vertical Test Pad B




CAPABILITIES:

- Ground level testing
- 1-36B pad, inactive

TESTING HISTORY:

- Titan III, 120 Inch Diameter,
Solid Strap On



DRAFT 24-Nov-00

Motor Behavior Complex

Area 1-36, Detonation Test Pad D



FACILITY CAPABILITIES:

- Data acquisition and control system
 - 24 channel high-speed Le Croy digital recorder, 300mHz
 - 28 channel frequency modulated tape recorder
 - PC based LABVIEW control system

TEST STAND CAPABILITIES:

- Ground level testing
- Storable and solid propellant
- Detonation, high hazard, and explosive studies
- 150 foot diameter cleared ground pad
- 1-36D pad, maximum explosive capability
 - 1M lbs TNT equivalent
- Ignition system
 - Standard 28 VDC
 - 5,000 VDC explosive bridgewire circuit




TESTING HISTORY:

- PeaceKeeper Flight Termination Stage III
- Ammonium Perchlorate
- Silo Fire Safety
- Space Launch Safety Studies
- Solid Propellant Hazards Study (SOPHY)
- Tool Drops on Minuteman Stage III

DRAFT 24-Nov-00

Motor Behavior Complex Area 1-36, Detonation Test Pad D



SuperHIPPO Motor Impact Studies 1992

DRAFT 24-Nov-00


Propellant Storage Area

Area 1-38



CAPABILITIES:

- 9 storage buildings
 - Each building 24 foot x 31 foot
 - 20 foot vertical clearance
- Sited for 50,000 lbs of 1.1 or 200,000 lbs of 1.3 TNT equivalent propellant
- Environmental capability
 - Temperature
 - Humidity





Liquid Propellant Aging Facility

Area 1-40




CAPABILITIES:

- Propellants stored since 1971
- 1,500 psi GN2 Cross country line
- 6 inch water main from area 1-14
- 440 VAC facility / stand power
- Mechanical shop

TEST STAND CAPABILITIES:


- Pad A / B - maximum thrust 5,000 lbf.
 - Current configuration; inactive
 - No thrust stand
- Pad C / D - maximum thrust 50,000 lbf.
 - Current configuration; inactive
 - No thrust stand
- Mechanical shop aging building
- Liquid propellant long term storage studies
 - CLF5 -- CLF3
 - Firex system
- Portable heating and air conditioning



TESTING HISTORY

- Bi-Propellant Oxidizer Feed System
- Tank Storability

DRAFT 24-NOV-00



Space Environment Propulsion Complex


Area 1-42

GENERAL AREA CAPABILITIES:

- Propane-fired steam / vacuum system
 - Altitude simulation to 120,000 feet (A,B,D cells)
 - 400 to 1800 seconds duration
 - Mass flow 600lb/sec EWA 70
 - 1,800,000 gallon water catch tank
- Mechanical pumped vacuum systems
 - Altitude simulation to 125,000 feet E cell
 - Altitude simulation to 650,000 feet SPEF chamber
- 6,000 psi GN2 cross country line
- 6 Inch water main
- 440 VAC and 28 VDC stand power
- Data acquisition and control system
 - 192 channel, 100,000 sample per second, data system
 - 256 channel programmable logic control system
- Mechanical shop with 2 ton crane

CELL CAPABILITIES: (current configuration)

- Altitude simulated testing
- A cell - 60,000 lbf. thrust, horizontal
- D cell - 20,000 lbf. thrust, horizontal
- B cell - 50,000 lbf. thrust, vertical
- SPEF chamber, no thrust



TESTING HISTORY

- Trident stage III • Star 30 • ASAS • Agena
- XLR-132 • Centaur • EEC • Small ICBM
- Minuteman III • Composite Polar Boss • StarTech
- MSTI I / II / III • Viper • Hughes TTM/STM
- KEW (Kinetic Energy Weapon) • Gossamer Structures
- High Altitude Supersonic Target (HAST)
- TRSM Navy Third Stage Rocket Motor 1997





DRAFT 24-N~~S~~pace Environment Propulsion Complex

Area 1-42



GENERAL AREA CAPABILITIES:

- Propane-fired steam / vacuum system
 - 3 parallel stage, ejectors, 9 steam bottles
 - 120,000 feet simulated altitude (A,B,D Cells)
 - 400 to 1800 seconds duration (9 Bottles)
 - Mass flow rates approximately 600 Lb/Sec EWA 70
 - 1,800,000 gallon water catch tank
- Mechanical pumped vacuum systems
 - 125,000 feet simulated altitude E cell
 - 650,00 feet simulated SPEF chamber
- 6,000 psi GN2 cross country line
- 6 Inch water main
- 440 VAC and 28 VDC stand power
- Data acquisition and control system
 - LABVIEW: 192 channel, 100,000 sample per second
 - 256 channel programmable logic control system
- Mechanical shop with 2 ton crane

TEST CHAMBER CAPABILITIES


- Altitude simulation testing
- Environmental conditioning
- A Cell - maximum thrust 60,000 lbf.
 - (Current configuration) 60,000 lbf. thrust, horizontal
 - Chamber 12 foot diameter x 28 foot long
 - 66 Inch diffuser (77 inch maximum)
 - Solid motors up to 66 inch diameter x 18 foot long
 - 2 each 5 ton overhead cranes
 - 30K of TNT equivalent propellant

TEST CHAMBER CAPABILITIES (CONT.)


- D Cell - maximum thrust 20,000 lbf.
 - Chamber 10.5 foot diameter x 25 foot long
 - (Current configuration) 20,000 lbf. f thrust, horizontal
 - No diffuser (55 inch maximum)
 - Solid motors up to 48 inch diameter x 18 foot long
 - 5 Ton overhead crane
 - 30K of TNT equivalent propellant
- B Cell - maximum thrust 50,000 lbf.
 - Chamber 16 foot diameter x 28 foot high
 - (Current configuration) 4,500 lbf. thrust, vertical
 - 44 Inch diffuser (44 inch maximum)
 - Solid motors up to 48 inch diameter x 15 foot long
 - 30K of TNT equivalent propellant
- SPEFchamber
 - Chamber 30 foot diameter
 - Solar simulation
 - LN2 cryogenic panels


TESTING HISTORY

- Trident stage III • Star 30 • ASAS • Agena
- XLR-132 • Centaur • EEC • Small ICBM
- Minuteman III • Composite Polar Boss • StarTech
- MSTI I / II / III • Viper • Hughes TTM/STM
- KEW (Kinetic Energy Weapon) • Gossamer Structures
- High Altitude Supersonic Target (HAST)
- TRSM Navy Third Stage Rocket Motor 1997



Space Environment Propulsion Complex Area 1-42






DRAFT 24

Space Environment Propulsion Complex

Area 1-42




Area Steam Run

DRAFT 24-Nov-00

Horizontal Test Chamber Area 1-42, A Cell

CAPABILITIES:

- Altitude simulation to 120,000 feet
- Maximum thrust 60,000 lbf., horizontal
 - (Current configuration) 60,000 lbf. thrust, horizontal
 - Onboard automatic calibration system 99.9% accuracy
 - Motor spin and IR measuring capability
 - Six component thrust capability
- Chamber 12 foot diameter x 28 foot long
 - 8 ft. diameter removable top, 12 ft. diameter clamshell door, 4 ft. x 6 ft. side access door
 - 2 each, 5 ton overhead crane
 - Film camera portholes (4), and in-chamber video (2)
 - 63 inch diffuser (77 inch maximum)
 - Solid motors Up to 32 inch diameter x 177 inch long
- 3,000 PSI test stand hydraulics
- Environmental conditioning
 - (0 to + 70 degrees F)
- 30K of TNT equivalent 1.1 class propellant




TESTING HISTORY

- Trident stage III • Composite Polar Boss 1990
- Minuteman III 1986 • Star 30
- Advanced Solid Axial Stage (ASAS)
- Extendible Exit Cone (EEC) 1980-1981
- High Altitude Supersonic Target (HAST) 1973
- Kinetic Energy Weapon (KEW)
- Advanced Integrated Stage (AIS) 1990
- Air Launched Space Booster 1979, 1983




DRAFT 24-Nov-00

Horizontal Test Chamber Area 1-42, A Cell




70 lb. Spin BATES

DRAFT 24-Nov-00




Horizontal Test Chamber Area 1-42, A Cell



Minuteman III, Stage 3, 1986


DRAFT 24-Nov-00

Horizontal Test Chamber Area 1-42, A Cell



Bell Aerospace Extendible Exit Cone (EEC), 1977

DRAFT 24-Nov-00




Vertical Test Chamber Area 1-42, B Cell



CAPABILITIES:

- Altitude simulation to 120,000 feet
- Maximum thrust 50,000 lbf., vertical, nozzle down
 - (Current configuration) 4,500 lbf. thrust
 - Onboard automatic calibration system 99.8% accuracy
 - Motor IR measuring capability
 - Six component thrust capability
- Chamber 16 foot diameter x 28 foot high
 - 16 ft. diameter removable top, 4 ft. wide x 6 ft. high side door at ground level
 - Film camera portholes and in-chamber video
 - 44 inch diffuser maximum
 - Solid motors up to 48 inch diameter x 15 foot long
 - 1000 lbf hoist in cell
 - 3,000 psig Stand Hydraulics
- Environmental conditioning
 - (0 to 70 degrees F)
- 30K of TNT equivalent 1.1 class propellant




TESTING HISTORY

- StarTech 1981
- Trident C4 1974
- TRSM Navy Third Stage Rocket Motor 1997
- XLR 132 1983-1992
- Agena 1975-1976


DRAFT 24-Nov-00

Vertical Test Chamber Area 1-42, Chamber B




Agena Engine
1975-1976

DRAFT 24-Nov-00




Vertical Test Chamber Area 1-42, Chamber B



XLR-132 Engine,
1983-1992


DRAFT 24-Nov-00



Vertical Test Chamber Area 1-42, Chamber B




0063#



XLR-132 Engine,
1991

DRAFT 24-Nov-00




(SPEF) Test Sphere Area 1-42, C Cell



CAPABILITIES:


- **Mechanical pumped vacuum system**
 - Altitude simulation to 650,000 feet
 - Rotary piston pumps, roots blowers, and diffusion pumps
- **SPEF operations building**
 - Houses the test sphere and control center
 - 60 feet x 110 feet x 51 feet high
 - 60 ton and 10 ton traveling overhead cranes
- **Sphere 30 foot diameter**
 - 19 foot diameter removable top hatch
 - 8 foot diameter side access hinged door
 - LN2 cryogenic shroud to (-190 degree C)
 - 20 foot diameter x 22 foot high (with end caps)
 - Radiant heat IR simulator (200 watts/square foot)
 - Earth albedo simulator (maintain +/- 5 degree C)
 - 18 foot diameter aluminum disk with 99 heater elements
 - Film camera portholes and in-chamber video
 - Test article maximums
 - 100,000 lbs, 16 feet x 16 feet x 20 feet
 - 100K of TNT equivalent 1.1 class propellant
- **Data acquisition and control**
 - 150 channel temperature data system
 - 256 channel programmable logic control system




TESTING HISTORY

- Hughes TTM And STM
- Gossamer Structures
- Miniature Sensor Technology Integration (MSTI) Satellite I / II / III
- Centaur 1966
- Direct Chemical Laser (DCL) 1970-1974
- LASER Program (MESA) 1970-1974
- Centaur Propellant Storability

DRAFT 24-Nov-00




(SPEF) Test Sphere Area 1-42




MSTI II, 1995

DRAFT 24-Nov-00



(SPEF) Test Sphere Area 1-42, C Cell



Hughes TTM/STM 1980




DRAFT 24-Nov-00

Horizontal Test Chamber Area 1-42, D Cell




CAPABILITIES:

- Altitude simulation to 125,000 feet
- Maximum thrust 20,000 lbf., horizontal
 - (Current configuration) 20,000 lbf. thrust, horizontal
 - Onboard automatic calibration system 99.9% accuracy
 - Motor spin and IR measuring capability
 - Six component thrust capability
- Chamber 10.5 foot diameter x 25 foot long
 - 10.5 ft. diameter clamshell door, 4 ft. x 8 ft. side door
 - 5 ton overhead crane
 - Film camera portholes and in-chamber video
 - No diffuser (55 inch diffuser maximum)
 - Solid motors up to 24 inch diameter x 182 inch long
- Environmental conditioning
 - (-30 to + 100 degrees F)
- 30K of TNT equivalent 1.1 class propellant



TESTING HISTORY

- Small ICBM
- Kinetic Energy Weapon (KEW)



DRAFT 24-NL **Large Motor Operations Complex** Area 1-52




GENERAL AREA CAPABILITIES:

- 6,000 psi GN2 Cross Country Line
- 8 Inch Water Main
- 440 VAC Facility and 28 VDC Stand Power
- Data acquisition and control system
 - 192 channel, 100,000 sample per second, data system
 - 256 channel programmable logic control system
- Mechanical Shop
- 2 Assembly Buildings

TEST STAND CAPABILITIES:


(Current Configuration)

- Pad A - 50,000 lbf. Thrust
 - Horizontal or Vertical Firing
 - Liquid Engines or Solid Motors
- Pad B - No Thrust Stand
 - Horizontal or Vertical Firing
 - Solid Motors
- Pad C - 5,000 Lbf. Thrust
 - Hydrostatic Bearing Test Rig
 - Horizontal Orientation
 - Liquid Hydrogen Operations
- Pad D - No Thrust Stand
 - 250 Horsepower Commercial Air Conditioning System
 - Refrigerant Operations



TESTING HISTORY

- Liquid Fluorine Engine. 1969
- Graphite Overwrap Vessel, 1990
- Minuteman III, PAN Nozzle, 1989-1991
- Short Length SuperHIPPO, (SLSH), 1977-1983
- Minuteman III, Stage 3, Advanced Nozzle, 1983-1991
- Minuteman III, Stage 2, 1983-1989
- PeaceKeeper, Stage 3, 1982 • Bull Pup, 1982
- F-16 Hydrazine Tank Test • Titan Cook Off, 1985
- STAR TEC, 1984-1985 • Kevlar Tank Tests, 1986
- Linear Areospace SR-71 Experiment LASRE, 1996
- Turbopump Component Technologies 1989-1996
- R134a Carrier Dual Use Technologies 1996-1997



DRAFT 24-Nov-88 Large Motor Operations Complex Area 1-52



GENERAL AREA CAPABILITIES:

- 6,000 psi GN2 Cross Country Line
- 8 Inch Water Main
- 440 VAC Facility and 28 VDC Stand Power
- Data acquisition and control system
 - 192 channel, 100,000 sample per second, data system
 - 256 channel programmable logic control system
- Mechanical Shop
- 2 Assembly Buildings

TEST STAND CAPABILITIES (Cont):


- Pad C - Maximum Thrust 250,000 Lbf.
 - (Current Configuration) 5,000 lbs. Thrust
 - Horizontal Orientation
 - Hydrostatic Bearing Test Rig
 - 70,000 lbs of TNT Equivalent Propellant
- Pad D - Maximum Thrust 250,000 lbf.
 - (Current Configuration) No Thrust Stand
 - 250 Horsepower Commercial Air Conditioning System
 - 70,000 lbs of TNT Equivalent Propellant
 - C/D Stand Assembly Building

TEST STAND CAPABILITIES:

- Ground Level Testing
- Environmental Conditioning
- Pad A - Maximum Thrust 250,000 lbf.
 - (Current Configuration) 50,000 lbf. Thrust
 - Horizontal or Vertical Firing
 - Assembly Building
 - 77,000 lbs of TNT Equivalent Propellant
- Pad B - Maximum Thrust 250,000 lbf.
 - (Current Configuration) No Thrust Stand
 - Horizontal or Vertical Firing
 - 77,000 lbs of TNT Equivalent Propellant


TESTING HISTORY

- Liquid Flourine Engine. 1969
- Minuteman III, Pan Nozzle, 1989-1991
- Short Length SuperHIPPO, (SLSH), 1977-1983
- Minuteman III, Stage 3, Advanced Nozzle, 1983-1991
- Minuteman III, Stage 2, 1983-1989
- Graphite Overwrap Vessel, 1990
- PeaceKeeper, Stage 3, 1982 • Titan Cook Off, 1985
- STAR TEC, 1984-1985 • Bull Pup, 1982
- F-16 Hydrazine Tank Test • Kevlar Tank Tests, 1986
- Linear Areospace SR-71 Experiment LASRE, 1996
- Turbopump Component Technologies 1989-1996
- R134a Carrier Dual Use Technology 1996-1997



Large Motor Operations Complex

Area 1-52



DRAFT 24-Nov-00


Rocket Motor Test Stand

Area 1-52, Test Stand A



CAPABILITIES:

- Ground Level Testing
- Storable, Cryogenic, and Solid Propellant
- 30' x 44' x 5' Concrete Pad
- 25 ft high, 6 ft thick, vertical, reinforced concrete walls
- Horizontal or Vertical Firing
- Maximum Thrust 250,000 lbf.
- (Current Configuration)
 - 50,000 lbf. Thrust Stand
 - Horizontal, Single Axis
- 4500 gallon DI water
- 28,000 gallon, 35 psig, LN₂ dewar
- 5000 gallon, 1500 psig, LH₂ run dewar
- 546 ACF, 6000 psig, GH₂ vessel
- 70,000 lbs of TNT Equivalent Propellant




TESTING HISTORY

- Liquid Fluorine Engine. 1969
- Minuteman III, PAN Nozzle, 1989-1991
- Short Length SuperHIPPO, (SLSH), 1977-1983
- Zirconium Replacement Studies, 1983-1985
- Minuteman III, Stage 2, 1983-1989
- Small ICBM (SICBM) 1989 • F-16 Hydrazine Tank Test
- Motor Influence 1977 • Joint Live Fire 1986
- Linear Areospace SR-71 Experiment LASRE, 1996



DRAFT 24-1 Large Motor Operations Complex, Pad A




Minuteman III, Stage 3, 1985




DRAFT 24-11-10

Large Motor Operations Complex, Pad A



Linear Aerospike SR-71 Engine, 1997

DRAFT 24-Nov-00




Large Motor Test Stand

Area 1-52, Test Stand B



CAPABILITIES:

- Ground Level Testing
- Storable and Solid Propellant
- 30' x 45' x 5' Concrete Pad
- Horizontal or Vertical Firing
- Maximum Thrust 250,000 lbf.
- (Current Configuration)
 - No Thrust Stand
- 70,000 lbs of TNT Equivalent Propellant



TESTING HISTORY

- Special High Performance Ignition Technology (SHIPIT). 1983
- Minuteman III, Stage 3, Advanced Nozzle, 1983-1991
- Minuteman III, Stage 2, 1983-1989
- PeaceKeeper Design Margin, 1988
- PeaceKeeper, Stage 3, 1982
- Titan Cook Off, 1985
- Bull Pup, 1982
- 84 Inch CHAR Motor, 1980-198


DRAFT 24-Nov-00

Large Motor Test Stand Area 1-52, Test Stand C



CAPABILITIES:

- Modified for High Pressure Cryogenic or Steel Bearing Material Testing
- Ground Level Testing
- Storable, Cryogenic, and Solid Propellant
- 28' x 30' x 5' Concrete Pad
- 2-ton monorail hoist runs throughout C/D pad
- Horizontal Orientation
- Maximum Thrust 250,000 lbf.
- (Current Configuration)
 - 5,000 Lbf Thrust Stand
 - Hydrostatic Bearing Test Rig
- 77,000 lbs of TNT Equivalent Propellant
- Hydrogen Burn Stack; 16 Lb/Mass Per Second




TESTING HISTORY

- Nose Tip Testing, 1972-1980
- Graphite Overwrap Vessel, 1990
- STAR TEC, 1984-1985
- Turbo Pump Component Technologies 1989-1996
- R134a Carrier Dual Use Technologies 1996-1997



ABRES Nositip Chamber Assembly, 1972 - 1980

DRAFT 24-Nov-00




Large Motor Test Stand

Area 1-52, Test Stand D

CAPABILITIES:

- Ground Level Testing
- Storable, Cryogenic, and Solid Propellant
- 28' x 30' x 5' Concrete Pad
- Horizontal Orientation
- Maximum Thrust 250,000 lbf.
- (Current Configuration)
 - No Thrust Stand
- 77,000 lbs of TNT Equivalent Propellant
- Tankage shared with C pad
 - Two 3920 gallon, 6000 psig, DI water
 - 21,850 gallon, 415 psig, LH₂ dewar
 - 1200 gallon, 6015 psig, LH₂ run dewar
 - 1000 gallon, 1000 psig, LOX run dewar
 - 500 gallon, 3700 psig, tri-wall, LF₂ run dewar
 - 299 ACF, 6000 psig, GH₂ vessel
 - 70 gallon, 3500 psig, N₂O₄ run tank
 - 25 gallon, 700 psig, N₂O₄ catch tank
 - 70 gallon, 3500 psig, MMH run tank
 - 25 gallon, 700 psig, MMH catch tank



TESTING HISTORY

- Kevlar Tank Tests, 1986
- Carrier Air Conditioner (ARPA), 1996



DRAFT 24-Nov-00

High Thrust Facility Area 1-56

GENERAL AREA CAPABILITIES:


- 6,000 psi GN2 cross country line, 6,000 psi
- 12 inch diameter water main to fill storage tank
- 1 Million gallon deluge water storage
 - 20-inch diameter water line from storage tank to pad
- 440 VAC and 28 VDC stand power

SHOPS:

- Control Sta., 5,000 sq. ft.
- Mechanical, 2 ea., 5,000 sq. ft.

TEST STAND CAPABILITIES:

- Ground level testing
- 100 ft. deep, 120 ft. wide, 8 ft. thick, reinforced concrete pad, 50 ft. high vertical wall
- Cryogenic; storable; solid
- Maximum thrust, 10,000,000 lbs
 - Current configuration
 - 450,000 lbf thrust, vertical, nozzle up, six-component
 - 400,000 lbf thrust, horizontal, six-component
 - Maximum downward displacement 15 degrees
- 2,500,000 lbs class 1, TNT equivalent
- 1000 gallon, 400 psig LOX run tank
- GN2 Vessels, 2 ea., 270 cu. ft., 6,600 psi
- 9000 gallon, 800 psig, hydrazine run tank
- 12,000 gallon, 800 psig, nitrogen tetroxide run tank



TESTING HISTORY


- Extended Length SuperHIPPO (ELSH)
- Big Dumb Booster (Low Cost, High Thrust, Space Shuttle Alternative)
- AMROC Hybrid 1995
- Railroad Tank Car (Propane Relief Valve)
- X-33 Launch Facility 1997




DRAFT 24-Nov-00



High Thrust Facility



Extended Length Super HIPPO, 1985



DRAFT 24-Nov-00

Satellite Test & Integration Facilities Area 1-90




DESIGNED CAPABILITY:

- Designed to hold three small satellites simultaneously
- 10,000 parts per million clean room capability
- Controlled temperature 70 to 78 degrees
- Relative humidity control
 - 30 to 50 Percent
- Static discharge protection
- Sealed corridors between buildings
- One-ton capacity overhead crane with load attenuating devices
- 34,900 square feet of test area

- Altitude simulations
- Vibration table
- Telemetry ground station

CURRENT CAPABILITY:

- Facility inactive
- Equipment removed



TESTING HISTORY:

- Miniature Sensor Technology Integration (MSTI) - MSTI 1, MSTI 2 & MSTI 3
- Advanced Concept Architecture Test (ACAT) - ACAT Vehicle
- Summer Undergraduate Research Fellowship Satellite (SURF SAT)

DRAFT 24-Nov-00

Blast Hazard Complex

Area 1-90, Test Pad 1-90



FACILITIES CAPABILITIES:

- Blast hazard capability converted to satellite test and integration complexes

TEST STAND CAPABILITIES:

- Historic
 - Ground level testing
 - Liquid propellant
 - Bare pad
 - 150,000 lbs TNT equivalent



TESTING HISTORY:

- Titan I, 1st Stage
- Saturn S4B
- Blast Hazard Studies for Apollo Program

DRAFT 24-Nov-00

Blast Hazard Complex

Area 1-90, Test Pad 1-95



FACILITIES CAPABILITIES:

- Blast hazard capability converted to satellite test and integration complexes

TEST STAND CAPABILITIES:

HISTORIC:


- Atlas first "fast" loading of LOX and RP-1 propellants



TESTING HISTORY:

- Atlas Propellant Loading

DRAFT 24-Nov-00



Silo Complex Area 1-100




FACILITIES CAPABILITIES:

- Facility inactive
- GN2, power available
- Mechanical shop

TEST STAND CAPABILITIES:

- Two silos, 26 feet in diameter
 - 86 feet deep
- Silos are inactive




TESTING HISTORY:

- Minuteman Tethered Launch
- PeaceKeeper Tethered Launch
- Leonid Storm 1997




DRAFT 24-Nov-00


Minuteman Tethered launch Test Area 1-100



DRAFT 24-Nov-00



Silo Complex Area 1-100



Leonid Storm Meteorite
Shower, NOV 1997

DRAFT 24-NOV-00

Large Engine Component/System Test Complex

Area 1-120




GENERAL AREA CAPABILITIES:

- 6,000 psi GN2 cross country line
 - Can be pumped up to 10,000 psi
- 6 Inch water main
- 440 VAC and 28 VDC Stand Power
- 3,500 psi stand hydraulics
- Ground level mechanical shop
 - With 5 to 10 ton traveling overhead cranes
- Additional mechanical shops beneath test stand
 - Small fabrication / repair
- Data acquisition and control system
 - 320 Channel, 100,000 sample per second

TEST STAND CAPABILITIES:

(CURRENT CONFIGURATION)

- Ground level testing
- Test stand 2 - A, thrust abutment, 45 degree down
 - GN2 run/storage; 6,000 psi, 5010 cubic feet
 - LO2 run tank; 8,500 psi, 2,000 gallon
 - LH2 run tank; 8,500 psi, 3,800 gallon
- Test stand 1 - A, 1.6M lbf thrust, nozzle down
 - GN2 run/storage; 4,500 psi, 2850 cubic feet
 - LO2 run tank; 165 psi, 75,000 gallon
 - LH2 run tank; 165 psi, 90,000 gallon
- Test stand 1 - B, inactive, nozzle down




TESTING HISTORY

- F-1 Thrust Chamber (5,000 Firings)
- F-1 Engines, 750 firings (early 60s and 70s)
- Atlas (System) Tests (1957 - 1959)
- F-1 Engines, 980 firings (early 60s and 70s)
- RS-68 EELV 1997 -

DRAFT 24-Nov-00

Large Engine Component/System Test Complex Area 1-120






DRAFT 24-Nov-97

Large Engine System Test Stand, Area 1-120, Test Stand 1-A

CAPABILITIES:


- 4,500 psi GN2 line, 2850 cubic feet storage
- 14 inch water main from lake bed wells
- 440 VAC and 28 VDC stand power
- 3,000 psig, 35 gpm, hydraulic system
- Access to the 2A mechanical shop
 - With 10 ton traveling overhead cranes
- 1,000,000 gallon, gravity fed, flame deflector water storage
 - 1,200,000 gallon catch basin
- 14 inch and 12 inch diameter FIREX supply, 800,000 gallon storage
- Data acquisition and control system
 - 320 channel, 100,000 sample per second
 - 2 each, 16 channel, 3,200,000 samples per second
 - 256 Channel Programmable Logic Control
- Ground level testing
- Test Article space: 32 ft by 32 ft by 32 ft
- Maximum thrust 2,000,000 lbf, nozzle down
 - (Current configuration) thrust stand
 - 1,600,000 lbf Axial Thrust
- LO2 Run System; 75,000 Gallon, 165 psi
- Fuel Run System; LH2/RP-1, 90,000 Gallon, 165 psi
 - 60,000 hp, high pressure GH₂ system, 10,000 psig
 - 24 inch diameter hydrogen burn stack
- 20,000 lb TNT Equivalent of 1.1 Propellant



TESTING HISTORY

- Atlas (System) Tests (1957 - 1959)
- F-1 Engines, 750 firings (early 60s and 70s)
- RS-68 EELV 1997 -






DRAFT 24-NV0000

Large Engine System Test Stand, Area 1-120, Test Stand 1-B



CAPABILITIES:

- 4,500 psi GN2 line, 2850 cubic feet storage
- 14 inch water main from lake bed wells
- 440 VAC and 28 VDC stand power
- Mechanical shop
- Additional mechanical shop beneath test stand
- Flame deflector for two engines side-by-side
 - 54 inch diameter flame deflector water line from Building
- Intact, unlined, flame deflector water reclamation pond
 - 3,000,000 gallon capacity
 - 8 inch diameter return line to Building 8792
- Data acquisition and control system from test stand 1A blockhouse
- Ground level testing
- Two position, nozzle down test stand
- Room for 30 ft. by 60 ft test article
- Maximum thrust 6,000,000 lbf, 4 F1 cluster, nozzle down
 - (Current configuration) inactive, no thrust stand
- 75,670 gallon, 165 psig, LO₂ run tank
- 60,000 gallon, 150 psig, RP-1 run tank
- 10 ton traveling first story crane
- 5 ton jib crane on top of stand
- 100,000 lb TNT equivalent of 1.1 propellant



TESTING HISTORY

- F-1 Engines, 980 Tests (early 60s and 70s)




DRAFT 24-NP-0000 Large Engine Component Test Stand, Area 1-120, Test Stand 2-A



CAPABILITIES:

- 6,000 psi GN2 cross country line
- 14 inch water main from lake bed wells
- 440 VAC and 28 VDC stand power
- 3,500 psi stand hydraulics
- Mechanical shop with 5 ton traveling overhead crane
- Data Acquisition and control system
 - 320 channel, 100,000 sample per second
 - 2 each, 16 channel, 3,200,000 samples per second
 - 256 channel programmable logic control
- Ground level testing
- Two position component test capability
 - Test article space roughly 40 ft by 30 ft in each position
- Maximum thrust 2,000,000 lbf, 45 degree down
 - (Current Configuration) no thrust stand
 - 1,500,000 lbf thrust takeout capability
- 16 inch diameter hydrogen flare stacks
- GN2 storage; 10,000 psi, 950 ACF
- GH2 storage; 10,000 psi, 1600 ACF
- GH2 storage; 6,000 psi, 470 ACF
- GHe storage; 6,000 psi, 1,810 ACF
- LH2 storage; 248 psi, 28,000 gallon shared with 1A
- LO2 storage; 35 psi, 29,490 gallon
- LO2 run tank; 8,500 psi, 2,000 gallon
- LH2 run tank; 6,000 psi, 3,800 gallon
- RP-1 run / storage 6,600 psi, 272 gallon




CAPABILITIES (cont.)

- 14 inch diameter FIREX line
- 20,400 lb TNT equivalent of 1.1 propellant

TESTING HISTORY

- F-1 Thrust Chamber (5,000 Firings)




DRAFT 24-Nov-00

Large Systems Complex Area 1-125



FACILITIES CAPABILITIES:

- 6,000 psi GN2 cross country line
- 14 inch water main
- 3 Mechanical shops
 - With 25 ton traveling overhead cranes
 - With environmental conditioning
- Water system
 - 3,000,000 gallon storage tank for flame deflector
 - 400,000 gallon storage tank for FIREX
 - Double lined catch basin. Water recycled back to 3,000,000 gallon storage in one shift.
 - 168,000 GPM total pumped water flow 65,000 GPM water flow by gravity feed alone




TEST STAND CAPABILITIES:

- Ground level testing
- (Current configuration)
 - Test stand 1 - C 1.6M Lbf thrust, nozzle down
 - Test stand 1 - D inactive, nozzle down
 - Test stand 1 - E inactive, nozzle down
 - Modified for hover testing requirements

TESTING HISTORY

- Titan 34D
- Saturn V
- SRM Booster
- Titan IV
- H1 Engine
- SRMU Booster
- Kinetic Kill Vehicle (KKV Prototype and Advanced)



DRAFT 24-Nov-00

Large Systems Complex Area 1-125




GENERAL AREA CAPABILITIES:


- 6,000 psi GN2 Cross Country Line
- 14 Inch Water Main
- 440 VAC and 28 VDC Stand Power
- 3 Mechanical Shops (High Bay Assembly Buildings)
 - 94 Wide X 115 Tall X 50 High
 - With 25 Ton Traveling Overhead Cranes
 - With Environmental Conditioning
- Data acquisition and control system
 - NEFF 620, 512 channel, 50,000 sample per second data acquisition system
 - 256 channel programmable logic control system
- Water system
 - 3,000,000 gallon storage tank for flame deflector
 - 400,000 gallon storage tank for FIREX
 - Double lined catch basin. Water recycled back to 3,000,000 gallon storage in one shift.
 - 168,000 GPM total pumped water flow 65,000 GPM water flow by gravity feed alone

TEST STAND CAPABILITIES:

- Ground Level Testing
- Test Stand 1C - Maximum Thrust 8.0M lbf.
 - Test Stand Idle Since 1974, Re-activated 1986
- Current Configuration
 - For TITAN IV Support
 - 1.6M lbf, Six-component Thrust Stand
 - Vertical, Nozzle Down
- Test Stand 1D Maximum Thrust 8.0M lbf.,
 - Test Stand Idle Since 1974
 - Vertical, Nozzle Down
- Test Stand 1E
 - Test Stand Idle Since 1975
 - Modified for Hover Testing Requirements
 - Added Adjacent Target Test Stand
 - Vehicle Integration Facility, With a Clean Room
 - Propellant Storage and Handling
 - Range Support for Fueling and Handling KKV's
 - Supported KKV (Prototype and Advanced)

Large Systems Complex Area 1-125





Titan SRM Test Facility

Area 1-125, Test Stand 1-C




CAPABILITIES:

- 6,000 psi GN2 cross country line
- 14 inch water main
- 440 VAC and 28 VDC stand power
- Mechanical shop
 - With 25 ton traveling overhead crane
 - With environmental conditioning
- 3,400,000 gallon deluge storage
 - Cooling water can be pumped at 168,000 gpm
 - 5,000,000 gallon catch basin
 - 400,000 gallon storage tank for FIREX
- Modified 1988 for Titan 34D
- Current Configuration for Titan IV

*Need to Add
Titan 34D
(nozzle)
11/20/00*

TEST STAND CAPABILITIES:


- Ground level testing
- Multi-story environmental conditioning
 - 40 to 90 degrees F, 40 percent relative humidity
- Test article volume estimated 60 by 57 by 120 ft
- Maximum thrust 8.0M lbf., nozzle down
 - Current configuration 6 component thrust stand
 - 2,500,000 lbf. thrust takeout
 - 1,600,000 lbf. axial thrust
- 690,000 lb of 1.3 class propellant



TESTING HISTORY

- Titan 34D, 1987
- Titan IV
- Saturn V
- SRM Booster
- SRMU Booster, 1992, 1993, 1999

DIVAF 1 24-Nov-00




Area 1-125, Test Stand 1-C



- Successfully Fired T34D SRM, 15 June 1987


DRAFT 24-Nov-00

Area 1-125, Test Stand 1-C




Titan IV SRMU Booster Railhead Delivery to AFRL, 1993

DRAFT 24-Nov-00



Area 1-125, Test Stand 1-C



Titan IV SRMU Booster Test Stand Delivery, 1993



DRAFT 24-Nov-00

Large Systems Complex

Area 1-125, Test Stand 1-D




FACILITIES CAPABILITIES:

- 6,000 psi GN2 cross country line
- 14 inch water main
- 440 VAC and 28 VDC stand power
- Mechanical shop
 - With 25 ton traveling overhead crane
 - With environmental conditioning


TEST STAND CAPABILITIES:

- Flame deflector
 - 46 ft inside width, 51.5 ft long, 56 ft deep
- Ground level testing
- Maximum thrust 8.0 M lbf., nozzle down
 - Current configuration; inactive, no thrust stand
- 90,000 gallon, vacuum jacketed, 165 psig LOX run tank
- 70,000 gallon, 165 psig, stainless steel, RP-1 run tank
- 760,000 lb of 1.3 class propellant



TESTING HISTORY

- Saturn V



National Hover Test Facility

Area 1-125, Test Stand 1-E



FACILITIES CAPABILITIES:


- 6,000 psi GN2 cross country line
- 14 inch water main
- 440 VAC and 28 VDC stand power

TEST STAND CAPABILITIES:

- Flame deflector
 - 46 ft inside width, 51.5 ft long, 56 ft deep
- Ground level testing
- Maximum thrust 8.0M lbf., nozzle down
 - Current configuration, inactive, no thrust stand
- 90,000 gallon, vacuum jacketed, 165 psig LOX run tank
- 70,000 gallon, 165 psig, stainless steel, RP-1 run tank
- 80,000 lb of 1.3 class propellant

HOVER FACILITY

- Mechanical shop converted to hover high bay and control room
- Kinetic kill vehicle (KKV) free flight environment
- Integrated instrumentation systems
 - Video trajectory tracking
 - Telemetry uplink and downlink
 - Precision laser velocity and position measuring system
 - Center of gravity and moment of inertia measurement
- Vehicle integration facility, with a clean room
- Range support for fueling / handling KKV's at remote locations
- External target test stand 80 meter and 800 meter distant



TESTING HISTORY

- 11 Different Vehicle Configurations
- Liquid and Solid Propellant Systems
- 26 Static Tests
- 16 Free Flight Tests

DRAFT 24-Nov-00


Hover Test Vehicles

ADDED SLIDE




ON TARGET

DATE: 1 AUG 89
 WEIGHT: 220 LB
 LENGTH: 75 IN



LEAP 1 PATHFINDER

DATE: 24 JUL 90
 WEIGHT: 40 LB
 LENGTH: 23.5 IN




HUGHES LIQUID

DATE: 18 JUN 91
 WEIGHT: 12.1 LB
 LENGTH: 16 IN



ROCKWELL LIQUID

DATE: 5 AUG 92
 WEIGHT: 40 LB
 LENGTH: 22.9 IN



BOEING SOLID

DATE: 14 APR 93
 WEIGHT: 16.5 LB
 LENGTH: 25.5 IN



DRAFT 24-Nov-00



Electric Propulsion Laboratory

GENERAL AREA CAPABILITIES:

- Mechanical, Diffusion, Turbomolecular, and Cryo Pumped Vacuum Systems
- Data Acquisition and Control System

TEST CELL CAPABILITIES:

- Two 600 Cubic Foot Arcjet Chambers
 - 8 Foot Diameter x 12 Foot Long Chamber
 - 50 kWe
 - 10-2 TORR Vacuum
 - Pumps 250 mg/sec Propellant
- 200 Cubic Foot Pulsed Plasma Chamber
 - 5 Foot x 8 Foot Long Chamber
 - 20 MWe Pulsed
 - 10-5 TORR Vacuum
- 2000 Cubic Foot Chamber (Planned)
 - 10 Foot Diameter x 20 Foot Long Chamber
 - 30 kWe
 - 10-6 TORR Vacuum
 - High Power Hall Thrusters




HISTORY:

- Ammonia 1995
- Hydrogen 1993-1996
- Carbon Based Propellant (Methane) 1995
- Electric Space Experiment (ESEX) 1995
- Collaborative efforts with; Loin Aerospace, NASA Lewis, and 6 Universities
- Teflon 1985-1996


DRAFT 24-Nov-00

Electric Propulsion Laboratory






Air Force Research Laboratory Fabrication Area



DRAFT 24-Nov-00



AFRL Fabrication Area Missile Assembly Building Building 8419



BUILDING CAPABILITIES:

- Four 25 Ton Overhead Cranes
- 17,000 Sq Ft of Work Space Under Crane Span
- Building is 60 Ft to Peak
- 40 Ft of Vertical Work Space Under Crane
- 8,000 Sq Ft of Office Space Adjacent to Work Space
- Building Originally Built for Missile Assembly
- Full Service Machine, Weld, and Fab Shops Nearby

